

# ΤΕΧΝΙΚΑ ΧΑΡΑΚΤΗΡΙΣΤΙΚΑ

## TORRENT ECO

| ΤΥΠΟΣ         | ΟΝΟΜ. ΙΣΧΥΣ ΚΑΤΑ ErP<br>2015 |       | ΜΕΓΙΣΤΗ<br>ΩΦΕΛΙΜΗ<br>ΙΣΧΥΣ | ΠΕΡΙΕΚΤΙΚΟΤΗΤΑ<br>ΝΕΡΟΥ | ΠΙΕΣΗ<br>ΛΕΙΤΟΥΡΓΙΑΣ | ΜΗΚΟΣ | ΔΙΑΤΟΜΗ/ΚΕΝΤΡΟ<br>ΚΑΠΝΟΔΟΧΟΥ | ΒΑΡΟΣ |
|---------------|------------------------------|-------|-----------------------------|-------------------------|----------------------|-------|------------------------------|-------|
|               | Kcal/h                       | Kw    |                             |                         |                      |       |                              |       |
| <b>SUN</b>    |                              |       |                             |                         |                      |       |                              |       |
| SUN 4         | 17.196                       | 20,0  | 41.255                      | 22,5                    | 4                    | 555   | Φ150 / 477                   | 170   |
| SUN 5         | 20.636                       | 24,0  | 51.204                      | 19,0                    |                      | 655   | Φ150 / 477                   | 199   |
| SUN 6         | 30.095                       | 35,0  | 61.101                      | 23,0                    |                      | 755   | Φ150 / 477                   | 226   |
| SUN 7         | 37.833                       | 44,0  | 69.828                      | 25,0                    |                      | 855   | Φ150 / 477                   | 256   |
| <b>GALAXY</b> |                              |       |                             |                         |                      |       |                              |       |
| GLX 4         | 20.199                       | 23,5  | 50.499                      | 23,0                    | 6                    | 661   | Φ150 / 400                   | 212   |
| GLX 5         | 31.161                       | 36,2  | 62.485                      | 29,0                    |                      | 782   | Φ150 / 400                   | 249   |
| GLX 6         | 48.151                       | 56,0  | 74.592                      | 35,0                    |                      | 903   | Φ180 / 400                   | 290   |
| GLX 7         | 64.488                       | 75,0  | 91.178                      | 41,0                    |                      | 1024  | Φ180 / 400                   | 330   |
| GLX 8         | 73.946                       | 86,0  | 107.902                     | 47,0                    |                      | 1145  | Φ180 / 400                   | 369   |
| <b>MATRIX</b> |                              |       |                             |                         |                      |       |                              |       |
| MTX 5         | 94.583                       | 110,0 | 129.407                     | 67,0                    | 8                    | 925   | Φ250 / 567                   | 529   |
| MTX 6         | 107.480                      | 125,0 | 165.004                     | 80,0                    |                      | 1055  | Φ250 / 567                   | 610   |
| MTX 7         | 124.677                      | 145,0 | 198.280                     | 93,0                    |                      | 1185  | Φ250 / 567                   | 863   |
| MTX 8         | 137.575                      | 160,0 | 229.493                     | 106,0                   |                      | 1315  | Φ250 / 567                   | 760   |
| MTX 9         | 150.473                      | 175,0 | 260.017                     | 119,0                   |                      | 1445  | Φ250 / 567                   | 834   |
| MTX 10        | 171.969                      | 200,0 | 290.026                     | 132,0                   |                      | 1575  | Φ250 / 567                   | 907   |
| <b>STAR</b>   |                              |       |                             |                         |                      |       |                              |       |
| STAR 6        | 120.378                      | 140,0 | 186.930                     | 73,0                    | 8                    | 998   | Φ250 / 420                   | 726   |
| STAR 7        | 154.772                      | 180,0 | 238.005                     | 85,0                    |                      | 1131  | Φ250 / 420                   | 832   |

|           |                                          |       |           |       |   |      |            |      |
|-----------|------------------------------------------|-------|-----------|-------|---|------|------------|------|
| STAR 8    | 189.166                                  | 220,0 | 288.908   | 97,0  |   | 1264 | Φ250 / 420 | 931  |
| STAR 9    | 223.560                                  | 260,0 | 344.798   | 109,0 |   | 1397 | Φ250 / 420 | 1029 |
| STAR 10   | 253.654                                  | 295,0 | 484.093   | 121,0 |   | 1530 | Φ250 / 420 | 1127 |
| STAR 11   | 297.450                                  | 325,0 | 429.923   | 138,0 |   | 1663 | Φ250 / 420 | 1225 |
| MEGA STAR |                                          |       |           |       |   |      |            |      |
| MS 7      | Δεν εμπήτουν στον<br>κανονισμό 813/2013. |       | 431.298   | 305,0 | 8 | 1440 | Φ350 / 600 | 2015 |
| MS 8      |                                          |       | 515.907   | 350,0 |   | 1620 | Φ350 / 600 | 2260 |
| MS 9      |                                          |       | 593.293   | 395,0 |   | 1800 | Φ350 / 600 | 2510 |
| MS 10     |                                          |       | 670.679   | 440,0 |   | 1980 | Φ350 / 600 | 2715 |
| MS 11     |                                          |       | 748.065   | 485,0 |   | 2160 | Φ400 / 600 | 2960 |
| MS 12     |                                          |       | 825.451   | 530,0 |   | 2340 | Φ400 / 600 | 3210 |
| MS 13     |                                          |       | 911.436   | 575,0 |   | 2520 | Φ400 / 600 | 3450 |
| MS 14     |                                          |       | 997.420   | 620,0 |   | 2700 | Φ400 / 600 | 3695 |
| MS 15     |                                          |       | 1.100.602 | 665,0 |   | 2880 | Φ400 / 600 | 3940 |
| MS 16     |                                          |       | 1.203.783 | 710,0 |   | 3060 | Φ400 / 600 | 4185 |